

Accessori e complementari

Fans FS and FA

Available in many sizes with free blowing air volumes from 1300 m³/h, 765 CFM to 6000 m³/h, 3532 CFM. A unique anti-spark impeller made from aluminium gives maximum security.



NOTE! ALL FANS MUST BE FITTED WITH RELEVANT MOTOR OVERLOAD PROTECTION (NOT INCLUDED).

Fan	Airflow Freeblowing m ³ /h, CFM	Motor kW V (50Hz)
1300	1300, 765	0,37 kW 3~ 400 V*
1301	1300, 765	0,37 kW 1~ 230 V*
1800	1800, 1059	0,55 kW 3~ 400 V*
2100	2100, 1236	0,75 kW 3~ 400 V*
2101	2100, 1236	0,75 kW 1~ 230 V*
3000	3000, 1766	1,10 kW 3~ 400 V*
4700	4700, 2766	2,20 kW 3~ 400 V*
6000	6000, 3532	4,00 kW 3~400 V*


* Other voltages and frequencies for motors are available.

Stanchion

Accessory for ceiling, floor or wall mounting of MultiSmart® Arm.

Length: 110 cm, 3.6 ft. **Prod. no PA-110**

Length: 220 cm, 7.2 ft. **Prod. no PA-220**



SmartArm Extension kit

Contains all necessary items to convert a 3 meter, (10 ft) arm to a 4 meter, (14 ft) arm.

Prod. no SAE-125-4

Prod. no SAE-160-4

Prod. no SAE-200-4



Halogen lamp cartridge

To be fitted in the hood. Consists of 20W/24 V halogen lamp, switch assembly and 10 m, (33 ft) cable. Must be complemented with transformer TR-24 or Starter SA-24.

Prod. no HL-20/24-125

Prod. no HL-20/24-160

Prod. no HL-20/24-200

* Not available in MSAS



Damper kit


Contains all necessary items to install a ratchet damper for fine tuning the airflow through the arm.

Prod. no D-125

Prod. no D-160

Prod. no D-200

* Is not available in MSAS




Transformer

230 V* – 24V/75 VA transformer for halogen lamp cartridge HL-20/24.

Prod. no TR-24/75

* Other voltages are available



Switch assembly

Switch assembly with 10 m (10 ft) cable for manual operation from the hood of fan and light. Also supplied as standard as part of ES-90 and ASE-12. Inkl.

Prod. no S-100




Fully automatic damper

Fully automatic motordriven damper for fitting to Ø 160 mm, 6" Ø duct. Adjustable overrun period between 7 sec. and 6 min., to capture after-fume. Inductive sensor with 5 m (16 ft) of cable is included as standard. Power supply: 1~ 230 V*. Can be complemented with switch assembly (S-100) for manual control.

Prod. no ASE-12

* Other voltages are available



Control unit

For automatic start/stop of a central fan in a system with several extractors. To be used in conjunction with the Energy Saver or Automatic Damper. Power supply: 3~ 230/400 V*.

Prod. no M-1000

* Other voltages are available



Energy Saver

For automatic start/stop of fan. Adjustable overrun period of between 7 sec. to 6 min. Incl. inductive sensor with 5 m, (16 ft) cable. Built-in contactor must be fitted with relevant fan-motor overload (not included). Power supply: 3~230/400 V*.

Prod. no ES-90-005 incl. 75 VA/24 V transformer for hood light.

Prod. no ES-90-006 incl. 75 VA/24 V transformer. For two arms with lights.

* Other voltages are available



Starter

For manual start/stop of the fan via a switch in the hood. Complete with switch assembly and 10 m, (33 ft) cable. Built-in contactor must be fitted with relevant fan motor overload (not included). Power supply: 3~ 230/400 V*.

Prod. no SA-24/75 incl. 75 VA/24 V transformer for halogene lamp on one workstation.

Prod. no SA-24/75-2 incl. 75 VA/24 V transformer for two halogene lamps on two workstations.

* Other voltages are available

